

# D\_P01\_07\_Matrix\_Siliconcompatibility\_GTG.xlsx

Designation GTG	Compatibility test of DOW according to ASTM C1087 or ETAG 002 paragraph 5.1.4.2.5							Compatibility summary of SIKA CQP593-8 (based on ASTM C1087) and CQP593-1 or -4 (based on EOTA ETAG 002)				
	DOWSIL 121 structural glazing sealant	DOWSIL 3362 Silicone Insulating glass sealant	DOWSIL 3363 Insulating glass sealant	DOWSIL 791 Silicone Wheaterproofing Sealant	DOWSIL 895 Structural glazing sealant	DOWSIL 993 structural glazing sealant	DOWSIL 795 silicone building sealant	Sikasil IG-25 HM Plus black	Sikasil SG-20 black	Sikasil SG-500 black	Sikasil SG-510 black	Sikasil WS-605 S black
Bau 60-3 M-1.00210.00.01	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	Pass	Pass	Pass	Fail	Pass
Bau 70-3 M-1.00211.00.01	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	Pass	Pass	Pass	Fail	Pass
Bau 80-3 M-1.00212.00.01	approved for full contact	approved for full contact	approved for full contact	approved for full contact	not approved for any application - not compatible	approved for full contact	approved for full contact in dark colors only	Pass	Pass	Pass	Fail	Pass
Bau 60 GTA M-1.00085.00	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact	Pass	Pass	Pass	Pass	Pass
Bau 70 GTA M-1.00218.01	approved for full contact	approved for full contact	approved for full contact	approved for full contact	approved for full contact in dark colors only	approved for full contact in dark colors only	approved for full contact in dark colors only	Pass	Fail	Pass	Pass	Pass
Bau Moos 35% Polym. 065 M-1.00277.00.01	approved for full contact	approved for full contact	approved for full contact	approved for full contact	not approved for any application - not compatible	approved for full contact	approved for full contact in dark colors only	Pass	Pass	Pass	Pass	Pass